

decotric Aqua-Deck White Insulating Paint

Aqua-Deck Isolierweiss E.L.F.

Special water based insulating for highly soiled indoor surfaces

Instructions for use:

decotric Aqua-Deck White Insulating Paint prevents nicotine, soot, fat and dry water marks from penetrating through, including the coloured contents of plaster boards, and covers yellowing on rigid foam panels such as expanded polystyrene (Styropor).

For wall and ceiling surfaces made of concrete, cement and lime cement plaster, masonry, gypsum substrates, fibre cement panels, also for adhesive dispersion plaster and wallpapers. Suitable as a final coating or can be covered over with wallpapers, dispersion colours and plasters.

Specially recommended for interior spaces that are quickly renovated and soon lived in or used again - for example in hotels.

Technical specifications:

Components:	pure acrylate resin, titanium dioxide, additives, filling compound
Density:	approx. 1.50 g/cm ³
Colour:	white
Usage:	approx. 150 ml/m ² per coat
Wet-scrub resistance	Class 2 – EN 13300
Scrubbing cycles:	> 5,000 DH, scrubbing resistant to EN13300
Gloss level:	dull matt
Contrast ratio:	Class 1 at a coverage of 7 m ² /l
Maximum grain size	fine

Surface preparation:

The surface must be dry, firm, and free of release agents (dust, etc.) Remove all traces of loose plaster, flaking remaining paint and old distemper paint. Prime highly absorbent, sanding and chalking surfaces using *decotric Deeply-Penetrating Primer LF* or *LH*.

Application:

Apply *decotric Aqua-Deck White Insulating Paint* unthinned using a solvent-resistant roller or a suitable airless spray gun.

Where the surfaces are highly soiled we recommend to apply a second coat. The first coat must be completely dried before the second coat of paint is applied (min. 12 hours).

Do not mix with other materials. Toning down is only possible using *decotric* toning down concentrate (only LW oxide types) up to a max. 0.2 % without impairing the sealing effect.

A relative humidity of 80 % must not be exceeded. Low temperatures and/or higher air humidity can delay drying and impair the sealing effect.

Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools with water immediately after use.

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Store in a cool and frost-free place! Keep the container tightly sealed.

Available sizes:

250 ml PE tub	014208001
750 ml PE tub	014201001
2,5 l PE tin	014202001
5 l PE tin	014203001
10 l PE tin	014204001