

# decotric fine waste paper

**Area of application:**

decotric Fine Maculature is ideal for preparing rough and grainy surfaces for wallpapering. Can be used on all mineral surfaces such as gypsum plaster, lime and cement plaster, concrete, etc. decotric Fine Maculature creates smooth, neutral and slightly absorbent surfaces for subsequent wallpapering.

**Properties:**

- Wallpapering substrate
- Smooths rough and grainy plaster
- Regulates absorbency
- Fills pores
- Ensures better adhesion and correctability of wallpaper

**Technical data:**

Raw material base: Wood flour, mineral components, modified starch  
 Density: approx. 0.46 g/cm³  
 pH value: 7 – 8

**Substrate preparation:**

The substrate must be dry, stable and free of release agents (dust, formwork oil, etc.). Remove old distemper paint and poorly adhering wallpaper. Prime highly absorbent, sandy and chalky substrates with decotric Tiefengrund LF primer. Repair cracks and holes with decomur Super-Haftspachtel or decofill Füllspachtel interior filler.

**Preparation:**

Slowly add decotric Fein-Makulatur to clean, cold water (see table) while stirring and continue stirring for a short time. After a swelling time of 30 minutes, stir the mixture vigorously again.

Application method	Amount of water per 1 kg
Brush application	6 l
Trowel application	4 – 5 l
Airless sprayer	8 l

**Application:**

Apply decotric Fine Maculature evenly to the substrate using a ceiling brush. For very rough or uneven substrates, decotric Fine Maculature can also be applied as a filler and smoothed with

a smoothing trowel or a surface filler. For large areas, decotric Fine Maculature can also be applied efficiently with a suitable airless sprayer. Under certain circumstances, the suitability must be checked with the equipment manufacturer. Allow the treated surface to dry completely before wallpapering. If necessary, the surface can be lightly sanded.

**Consumption:**

Depending on the substrate condition and application method, 1 kg is sufficient for approx. 20–25 m².

**Notes:**

Clean tools with water immediately after use.

**Storage:**

Store containers tightly closed in a cool, dry place. Keep out of reach of children.

**Disposal:**

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of product residues according to EWC waste code no. 08 04 14.

**Item no.** 004002001      **EAN** 4007955040026      **Container size** 1 kg



**Note**

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the suitability of the products for their intended use under the respective conditions.