

decotric Adhesive for Designer Flooring

Use:

For reliable and durable bonding of designer coverings. Also suitable for non-absorbent substrates, e.g. PVC.

Properties:

- for LVT and vinyl
- short flash-off time
- very high bond strength
- solvent-free
- very-low-emission to EC 1 plus
- suitable for chair castors to DIN EN 12529
- suitable for floor heating systems

Technical data:

Raw material Polymer dispersion, natural resin base: derivatives, mineral components, water, additives

Density: Approx. 1.3 g/cm³

pH value: 7 - 8

Substrate preparation:

Product is suitable for moisture-resistant substrates, e.g. V100 particleboard, PVC and CV coverings, tiles, screeds etc. Substrate shall be permanently dry, strong, level and free from cracks, adhesion-impairing substances and soiling (e.g. dust, grease). Application of floor levelling compound is recommended for rough or uneven substrates. Prime highly absorbent and friable substrates, e.g. with decotric All-purpose Primer or decotric Primer – solvent-free. Coverings to be bonded shall be acclimatized and stress-free, and shall lie flat.

Application:

Uniformly apply adhesive to substrate with notched spatula (class A1 or A2 serration, depending on specifications of covering manufacturer) and, after short flash-off time, place covering into adhesive bed and press down. Flash-off time is approx. 10 minutes, depending on substrate suction, temperature and humidity. Observe minimum flash-off time of 30 minutes in case of non-absorbent substrates (e.g. PVC); where appropriate, allow longer times in unfavourable conditions (e.g. low room temperatures or high humidity).

Consumption:

Approx. 200 - 300 g/m²

Note:

Observance of covering manufacturer's laying guidelines is essential. Do not use at building fabric and room temperatures below +10 °C. Immediately remove adhesive residue with water. Wash tools with water immediately after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.decotric.de or from sds@decotric.de.

Storage:

Store in cool, though frost-free environment in properly sealed containers. Keep out of reach of children.

Disposal:

Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 04 10.

Item No.	EAN	Container size
005702001	4007955057024	3 kg
005703001	4007955057031	5 kg



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.