

decomur Light Filler

Area of application:

Ready-to-use, solvent-free filler for repairing and smoothing uneven wall and ceiling surfaces indoors. The smooth filler is very easy to smooth and, once dry, can be sanded to a high finish if required. The filled surface provides an ideal base for subsequent wallpapering and painting work. Ideal for filling gypsum, lime and cement plaster, concrete, plasterboard and other drywall panels, synthetic resin plasters and painted surfaces. Thanks to its high stability and low sagging, the filler is also ideal for filling textured plaster surfaces and glass fibre mesh.

Features:

- Extra easy application and smoothing
- Optimal results on plaster, concrete, plasterboard and painted surfaces
- very easy to sand
- For indoor use
- Can be stretched to zero
- For surface qualities Q1-Q4 in drywall construction

Technical data: Raw material base: Plastic dispersion, inorganic lightweight fillers, water and additives

Density approx. 1.3 g/cm³
pH value: 8 - 9

Substrate preparation:

The substrate must be dry, sound and free of release agents (dust, grease, etc.). Prime highly absorbent, sandy and chalky substrates with decotric Tiefengrund LF. Fill deeper holes and cracks with decomur Super-Haftspachtel. When filling plasterboard and other drywall panels, apply the base coat according to Q1 using decomur Super-Haftspachtel.

Application:

Stir the filler and apply it with a smoothing trowel, for example, to a maximum layer thickness of 8 mm. Depending on the thickness of the application, the condition of the substrate and the ambient conditions, the drying time is approx. 4–7 hours; in unfavourable conditions (e.g. low temperature or high humidity) and with high layer thicknesses, the drying time may be longer. After drying, the filled surfaces can be wallpapered, painted over or covered with adhesive in the usual manner. If necessary, the dried surface can be sanded very easily. Before further work, dust the sanded surface thoroughly and prime with decotric Tiefengrund LF.

Notes:

Do not process at object and room temperatures below +5 °C. Clean tools with water after use. In case of contact with eyes, rinse immediately with plenty of water. Do not allow to enter drains, water or soil. Not suitable for filling work on glass, plastic and metal.

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website www.decotric.de or at sds@decotric.de.

Storage:

Keep containers tightly closed and cool, but not frozen. Keep out of reach of children.

Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues in accordance with EWC waste code no. 08 04 10.

Item no.	EAN	Container size
032502001	4007955325017	7 kg
032503001	4007955325031	15 kg



Note:

All information and data in this information sheet correspond to our practical experience and laboratory tests and are based on the current state of technology. However, they can only provide general information and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal liability can be derived from this information. It is the responsibility of the user to check the products for their suitability for the intended use under the respective conditions.