

decofill Exterior decofill aussen

Weather resistant, synthetic resin reinforced cement-smoothing compound for use indoors and outdoors.

Instructions for use: decofill Exterior is suitable for improving, smoothing and coating mineral surfac-

es-e.g. lime, cement and gypsum based plaster, concrete, air-entrained concrete, clay tiles, etc. - as well as laying ceramic tiles. The filled areas are easy to

smooth and felt.

Not suitable for filling works on wood, metal, plastic, glass and coats of emul-

sion paint.

Technical specifications: Components: White cement, powdered synthetic resin, cellulose

ether, fillers and additives

Density: approx. 1.35 g/cm³

pH-value: 12-13

Mixing ratio: 2.3 parts by volume of powder to 1 part by volume

of water (e.g. 1 kg powder with 300 ml water)

Usage: 1.2 kg powder for 1 m² and 1 mm thick layer

Working time: 4-5 hours

Low in chromates according to EN 1907/2006 annex XVII (47)

Surface preparation: The surface must be firm and free from release agents (dust, formwork oil, etc.)

Remove flaking paints and loose plaster. Prime very smooth concrete as well as highly absorbent, sanding and chalking surfaces with decotric Deeply Penetrat-

ing Primer – Solvent Free or LH Universal.

Application: Pour clean, cold water into a container and sprinkle in decofill Exterior. Stir

vigorously until a smooth, lump-free mortar results. The stirred filler compound can be used for up to 4 hours. Unevenness can be smoothed or felted while

moist before the filler has completely set.

Do not carry out subsequent works (painting, gluing, drilling, etc.) until the filled area has completely dried. Always observe the paint and adhesive manufacturer's instructions for the pre-treatment of cement bound surfaces (e.g. fluorinate

with OLAFIRN).

Do not use if the surface and/or room temperature are below +5° Celsius.

Clean tools in water immediately after use.

Important information: Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)

CE-Regulation about detergents (No 648/2004):

Is not subject to the CE-Regulation

Is not subject to ADR

Storage: Store in a dry place! Keep the containers tightly sealed!

catalogue no.:

Available sizes: 003102001 1 kg collapsible box

003103001 5 kg paper bag