

decomur Deep Filler

decomur Tiefenfüller

Area of application:

Ultra-light, extra-white filler. Thanks to its high stability, the deep filler can also be applied in thicker layers and hardens without sinking or cracking. The material remains slightly flexible even after hardening, but is still easy to sand. Ideal for large cracks and breakouts, cable slots, junction boxes, pipe penetrations, deep and large dowel holes. For concrete, plaster and masonry, plasterboard, ceiling panels and decorative elements made of Styrofoam®, insulation boards, wood and chipboard. Styropor®-registered trademark of BASF

Properties:

- 4 cm in one step
- · No shrinkage
- Fast drying

Technical data: Raw material base:Plastic dispersion,inorganic 10. lightweight fillers, water and additives

Density approx. 0.4 g/cm³

pH value: approx. 7

Substrate preparation:

The substrate must be dry, stable, dust-free and free of grease. Prime highly absorbent, sandy and chalky substrates.

Application:

Press the deep filler firmly into the area to be repaired and smooth it off. Once hardened, the deep filler can be painted over with emulsion paints and acrylic lacquers.

Notes:

Do not use below +5 °C. Clean tools with water immediately after use.

Please refer to the safety data sheet for safety-related information. Current safety data sheets are available on our website www.decotric.de or atsds@decotric.de .

Storage

Store containers tightly closed and in a cool place, but not exposed to frost. Keep out of reach of children.

Disposal:

Only recycle containers that are completely empty. Dried material residues can be disposed of with household waste or as construction site waste. Dispose of uncured residues in accordance with EWC waste code no. 08 04 10.

 Item no.
 EAN
 Package size

 025412001
 4007955254027
 750 ml



As of: 19 May 2020