

decotric Styrofoam Filler Styropor-Fueller

For jointing and repairing decoration elements, plaster mouldings and moulding patterns made of styro-foam and rigid-foam. For indoors.

Instructions for use:

decotric Styrofoam Filler is ideally suited for jointing and repairing decoration elements plaster mouldings and moulding patterns made of styrofoam and rigid-foam. Also suitable for jointing interior insulation boards. The filler remains slightly elastic and can be sanded and painted after complete drying. prevents formation of thermal bridges.

Technical information:

Components:	synthetic resin dispersion, special filler, additives, preservatives
Colour:	white
Density:	approx. 0.52 g/cm ³
pH-Value:	approx. 8

Application:

decotric Styrofoam Filler can be applied up to a thickness of max. 15 mm without cracking or shrinking. After completely drying (approx. 8 hours depending on thickness, room temperature and humidity) the material remains slightly elastic and can be sanded very easily. After completely hardening *decotric Styrofoam Filler* can be painted over with all commercial emulsion and acrylic paints.

Important information:

Do not use if the temperature of the room or substrate is below 5°C.
Clean tools with water immediately after use.

Contains preservatives: Methylchloroisothiazolinones/Methylisothiazolinones (3:1), Benzoisothiazolinones
May produce an allergic reaction.

Storage:

Store childproof in a cool, but frost-free place! Keep the containers tightly sealed! For a short term temperature resistant to -15°C.

Article no.:

024201001

Available size:

310 ml cartouche