

decotric Isolating Paint

decotric Isolierfarbe

Isolating paint to protect against damp and efflorescence on mineral surfaces, for indoor and outdoor use.

Instructions for use: *decotric Isolating Paint* isolates water, nicotine and soot stains. Prevents salt efflorescence on all mineral surfaces, such as concrete, lime and cement-based plaster, clay tiles, etc.
decotric Isolating Paint is not suitable for gypsum surfaces and gypsum boards, which are not permanently dry.

Technical specifications:

Components:	Acrylic resin, pigments, cement, solvent
Density:	approx. 1.15 g/cm ³
Colour:	white
Gloss level:	matt
Flash point:	approx. 57° Celsius
Usage:	150-200 ml/m ² per coat

Surface preparation: The surface can be moist, however, it must be firm and free of release agents. Remove efflorescence mechanically (brush) or using *decotric Saltpetre Remover*.

Application: Stir *decotric Isolating Paint* well before use and apply using a brush or paint roller. Always apply two coats to achieve optimum isolation of the surface. Leave the first coat to dry for at least 8 hours before applying the second.

Do not mix *decotric Isolating Paint* with other paint systems however, can be thinned with max. 5 % white spirit to adjust its consistency. After the isolating paint has thoroughly dried, all cement-resistant paint systems can be used on it.

Do not use at surface or in rooms below + 5° Celsius!

Clean tools immediately after use using *decotric Brush Cleaner* or *aka soluwash S*.

Important information: Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage: Store in a cool place! Keep containers tightly sealed! Keep away from bare flames and ignition sources.

Available sizes:

750 ml tin box	014401001
2 l tin tub	014402001