

## decotric Leaching and Degreasing Spray

decotric Anlauger und Entfetter - Spray

Ready-to-use and solvent-free surface treatment before any re-lacquering work.

Instructions for use: decotric Leaching and Degreasing Spray is the ideal surface treatment before

re-lacquering windows, doors, radiators, etc.. Grease, dirt, soot, nicotine, etc. are removed and a secure adhesion surface with maximum grip created. decotric Leaching and Degreasing Spray excellently removes grease, dirt and nicotine from lacquered and galvanised surfaces, tiles and plastics of all kinds, for example, from garden furniture, window frames, etc.. Particularly suitable for

cleaning inaccessible surfaces which cannot be ground (e.g. radiators).

**Technical data:** Components: Surfactants and phosphates

Density: 1.01 g/cm³ pH value: approx. 10.80 Consumption: 50-100 ml/m²

Application: Spray on decotric Leaching and Degreasing - Spray and thoroughly rinse using

clear water after a contact time of approx. 10 minutes. Clean galvanised surfaces using a plastic abrasive fleece and also rinse with clear water

thoroughly.

Cover glass and metal parts prior to treatment. Protect surfaces which are not to be treated from atomized spray and splatters. Immediately remove any

splatters with water.

Clean any working equipment with water immediately after use.

**Important information:** Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage: Store in a cool, but frost-free place. Keep the containers tightly sealed!

Available sizes: PE spray bottle with 500 ml each 024902001