

decotric Intensive Paint Stripper

decotric Intensiv Abbeizer

Stripping agent for paints and varnishes.

CHC and NMP free*

Instructions for use:

decotric Intensive Paint Stripper removes quickly and powerfully synthetic resin varnishes, acrylic varnishes, coats of oil paint, glazes, emulsion paint and latex paints and similar coatings. Does not damage surfaces made from wood, metal or masonry. Carry out a trial on a small area of surfaces sensitive to solvents first (plastics, etc.).

Technical specifications:

Components:	Ester, benzine, additives
Density:	approx. 1.0 g/cm ³
Usage:	approx. 300-600 g/m ²

*Additional information:

CHC = chlorinated hydrocarbons
NMP = N-methyl pyrrolidone

Application:

Apply *decotric Intensive Paint Stripper* with a brush or spatula to the surface to be stripped and leave until the painted or varnished layer has softened. The reaction time is between 15 and 30 minutes. By critical coats: cover the treated area with a plastic foil and leave for several hours.

Protect the areas treated with stripper from direct sunlight. Lift the partly dissolved paint layer using a stopping knife, collect in a container and deposit in the collection point for special wastes (paints and varnishes). Rub down the stripped surface using cloths soaked in solvent (white spirit, thinner) or directly wash off with water.

Clean all stripped surfaces with plenty of water.
Clean tools with water immediately after use.

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Store in a cool place! Keep the containers tightly sealed and keep away from ignition sources!

Available sizes:

750 g PE bottle	015402001
2.5 l PE bottle	015403001