

decotric Water Stop decotric Wasser-Dicht

Fibre-reinforced, permanently elastic sealing compound for durably sealing against penetrating water.

Instructions for use:	<p><i>decotric Water Stop</i> is suitable for quickly repairing leaking, even wet areas on roofs, terraces, masonry, etc. <i>decotric Water Stop</i> bonds with all common materials are used in construction, e.g. bitumen, roof tiles, roofing felt, aluminium, copper, zinc, concrete, clay tiles, tiles, wood, etc. Bridges cracks up to max. 10 mm. Not suitable for polystyrene.</p>	
Technical specifications:	Components:	Polyacrylic fibres, alkyd resin, solvent
	Density:	approx. 1.05 g/cm ³
	Colour:	grey
	Usage:	1.5 kg/m ²
Surface preparation:	<p>The surface must be firm and free of release agents. Mechanically remove dirt, loose masonry, moss and other growth. Non-firm surfaces such as sanding, brittle plaster has to be primed using <i>decotric Primer LF or LH</i> first.</p>	
Application:	<p><i>decotric Water Stop</i> is ready for use and should never be thinned. It can be applied using a brush or a stopping knife. When applying the product ensure that the surface is closed and a min. layer thickness of 2 mm is achieved. If the product is applied to a moist surface or during poor weather conditions (low temperatures, rain, etc.), apply a second coat within one week at the latest. The surface can be painted over with acrylic paints after 12-24 hours (depending on the weather conditions).</p> <p>Do not use if the surface temperature is below -5° C or above +35° C. Clean tools after use with <i>decotric Brush Cleaner</i>.</p>	
Important information:	<p>Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).</p>	
Storage:	<p>Keep container tightly sealed and store in a cool place. Keep away from naked flames and other ignition sources.</p>	
Available sizes:	375 ml tin	012801001
	750 ml tin	012802001