

Façade Impregnation “SILIFIRN L”

Ready to use, solvent-containing siloxane façade impregnation

Instructions for use:

SILIFIRN L can be used as a water repellent impregnation for mineral substrates. *SILIFIRN L* coats the surface with a thin, transparent, non-sticky silicon layer, which does not restrict the diffusion of water vapour and does not change the appearance of the treated material.

SILIFIRN L is suitable for use on the following surfaces: Cement and lime facing, stone, brickwork, concrete, foam mortar, sand-lime brick and lime, cement and silicate based coatings. Not suitable for gypsum based materials.

The considerable reduction in water absorption protects the treated area from frost damage and dirt and reduces heating costs.

Technical information:

Components:	Silane / siloxane, isoparaffins	
Density:	approx. 0.75 g/cm ³	
Flash point:	62° Celsius	
Coverage per m ² for 2 coats:	Sand-lime brick: approx.	approx. 0.4 l/m ²
	Foam mortar: approx.	approx. 1.0 l/m ²
	Sandstone: approx.	approx. 0.3 l/m ²
	Exposed concrete:	approx. 0.4 l/m ²
	Mineral plaster:	approx. 0.5 l/m ²

Surface preparation:

The substrate must be dry, stable and free of grease, forming oil etc. Moss or lichen covered areas should be treated with *decotric STOP Algae and Mould*.

Application:

Apply two coats of *SILIFIRN L* from top to bottom using a brush or a suitable spray system wet-in-wet. The second coat can be applied as soon as any glossy areas of the first coat have disappeared. Small parts can simply be dipped in *SILIFIRN L*.

Clean tools with water immediately after use.

Important information:

Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage:

Store in a cool place! Keep the container tightly sealed. Keep away from sources of ignition!

Available sizes:

1 l PE bottle	014801000
2.5 l PE canister	014802000
5 l PE canister	014803000
10 l PE canister	014804000