

Power Paste Normal Paper

Instructions for use: *Power Paste Normal Paper* is suitable for pasting light weight wallpapers.

Technical specifications:

Components:	Modified starch, methyl cellulose, additives
Density:	approx. 0.40 g/cm ³
pH-value:	approx. 8
Solubility:	Ready for use in 30 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using *decotric Wallpaper Remover*. Make good cracks and holes using *decofill Interior* or *decomur Super Bonding Filler*.

Pre-treat highly absorbent, sanding and chalking surfaces using *decotric Deeply Penetrating Primer – Solvent Free*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. We recommend applying a sub-coat of *decotric Wallpaper Primer - white* before hanging highly translucent wallpapers and where surfaces are highly contrasting.

Instructions for use: Stirring vigorously, sprinkle *Power Paste Normal Paper* into clean, cold water and continue to stir for a few minutes. Leave for approx. 30 minutes and then stir vigorously again.

Evenly apply *Power Paste Normal Paper* to the wallpaper using a brush fold the pasted ends inwards and hang after an adequate soaking time.

Hang the wallpaper according to the manufacturer's instructions.
Do not use if the surface and room temperature are below + 5° Celsius!
Remove adhesive residues using a damp cloth.
Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 125 g packet	Coverage of a 125 g packet
Pre-pasting	1 : 65	8 l	60-80 m ²
Lightweight wallpapers	1 : 52	6-7 l	30-35 m ²

Storage: Store in a cool and dry place!

Available size: 125 g collapsible box 002801173

Minimum durability: 5 years as of date of manufacture