

Power Universal Pink Control Indikator

Instructions for use:

Power Universal Pink Control Indikator is ideally suitable for pasting light and heavy woodchip wallpapers, paper wallpapers, vinyl wallpapers and non-woven wallpapers on mineral surfaces and gypsum boards

Technical specifications:

Components: Starch ether, poly vinyl acetate powder
Density: approx. 0.3-0.4g/cm³
pH-value: approx. 8-9
Solubility: Ready for use after approx. 5 minutes
Usage: approx. 200 ml/m²

Substrate preparation:

The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using decotric Wallpaper Remover. Make good cracks and holes using Power MT 75. Pretreat highly absorbent, sanding and chalking surfaces using decotric *Deeply Penetrating Primer – Solvent Free* or *Power Primer PP*. Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *decotric Insulating Spray*. We recommend a first coat with *decotric Wallpaper Primer* or *Power Primer PP* if hanging highly translucent wallpapers and where surfaces are highly contrasting.

Application:

Stirring vigorously, sprinkle *Power Universal Pink Control Indikator* into clean, cold water and continue to stir for some minutes. Leave for approx. 5 minutes and then stir vigorously again. The prepared adhesive with a pleasant lemon aroma is pink coloured to the make an evenly applying to the wallpaper easier.

Applying to wallpaper:

Evenly coat the wallpaper with *Power Paste Non-woven* and fold the pasted ends together. After leaving to soften for sufficient time, hang the wallpaper with matching seams and press down.

Applying to the surface:

Use a lambs wool roller to evenly apply the mixed Power Paste Non-woven to the surface over a width of 1-2 wallpaper widths. Place the wallpaper strip directly into the fresh adhesive bed and uniformly press down.

After dryness, the adhesive is transparent.

Always observe the wallpaper manufacturer's instructions for use.

We recommend to add *Power MT 75* for use on hardly absorbent surfaces and to increase the moisture resistance.

Remove adhesive residues using a damp cloth.

Do not use if the object and room temperature are below + 5° Celsius!

Clean tools in water after use.

Mixing ratio:

for	Mixing ratio	Quantity of water per 250-g packet	Coverage of a 250-g packet
pre-pasting/ priming	1:40	10 l	40-44 m ²
light paperbacked wallpapers	1:30	7,5 l	ca. 35 m ² ca. 7 rolls
heavyweight wallpapers and reinforcing fabrics	1:20	5 l	25-35 m ² 5-7 rolls

Storage:

Store in a cool and dry place!

Available size:

250 g collapsible box
022405026

Shelf life:

Min. 5 years as of production date.
Date of manufacture – see print

Shelf life:

Min. 5 years as of production date.
Date of manufacture – see print

