

Power wallpaper paste Universal

Instructions for use:	<i>Power Wallpaper Paste Universal</i> is suitable for pasting all paper-backed and heavy wallpapers, vinyl wallpapers, also for dry-strippable wallpapers as non-woven.			
Technical specifications:	Components:	Starch ethe	r, polyvinyl acetate po	owder
	Density:	approx. 0.3	5 g/cm³	
	pH-value:	approx. 9		
	Solubility:	Ready for u	ise after 5 minutes	
	Usage:	approx. 200) ml/m²	
Surface preparation:	The surface must be dry, firm, and dust and grease-free. Remove old, peeling wallpapers and distempers using <i>decotric Wallpaper Remover</i> . Make good cracks and holes using <i>decofill Interior</i> or <i>decomur Super Bonding Filler</i> . Pre-treat highly absorbent, sanding and chalking surfaces using <i>decotric Deeply Penetrating Primer – Solvent Free</i> . Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using <i>decotric Insulating Spray</i> . We recommend a first coat with <i>decotric Wallpaper Primer white</i> if hanging highly translucent wallpapers and where surfaces are highly contrasting.			
Application:	 Stirring vigorously, sprinkle <i>Power Universal</i> into clean, cold water and continue to stir for a few minutes. Leave for 5 minutes and then stir vigorously again. <u>Applying to wallpaper:</u> Evenly coat the wallpaper with ready mixed paste and fold the pasted ends together. After leaving to soften for sufficient time, hang the wallpaper with matching seams and press down. <u>Applying to the surface:</u> Use a lamb's wool roller to evenly apply the mixed paste to the surface over a width of 1-2 wallpaper widths. Place the wallpaper strip directly into the fresh adhesive bed and uniformly press down. Always observe the wallpaper manufacturer's instructions for use. We recommend to add 2 x 750 g <i>decotric Wallpaper and Border Adhesive</i> per 500 g packet for use on hardly absorbent surfaces and to increase the moisture resistance.			
	Do not use if the surface and room temperature are below + 5° Celsius! Remove adhesive residues using a damp cloth. Clean tools in water after use.			
Mixing ratio:	for	Mixing ratio	Quantity of water per 500-g packet	Coverage of a 500-g packet
	Pre-pasting	1:40	81	40-44 m ²
	All types of light paper backed wallpapers	1:30	61	approx. 30 m ² 6 rolls
	All types of heavy weight wallpapers	1:20	4	20-22 m ² 4-5 rolls
Storage:	Store in a cool and dry place!			
Available sizes:	200 g box 500 g box 1 kg box	022110026 022101026 022104026 022105026 022106026		
Minimum durability:	5 years as of date of manufacture			