

decotric Power MT 75

- filling and smoothing
- for gypsum boards
- for mineralic surfaces
- 0 – 15 cm
- indoors

Instructions for use:

decotric Power MT 75 is a white gypsum filling compound that is excellently suited for full-surface smoothing of walls and ceilings, for stopping joints in precast-concrete units and for filling cracks and holes. Also ideal for jointing and filling stressfree drylining board assemblies, for surface qualities Q1-Q4.

Suitable for mineral substrates (e.g. cement render, gypsum plaster, concrete, aerated concrete and masonry) and for gypsum plasterboard, gypsum fibreboard, cement fibreboard and similar drylining board to EN 13963.

Technical specifications:

Components: Gypsum, synthetic resin powder, methyl cellulose, additives
Bulk Density: 830 kg/m³
Usage: 1 kg powder per m² at a layer thickness of 1 mm

Substrate preparation:

The surface must be dry, strong and free from adhesion-impairing substances (e.g. dust, mould oil). Pretreat highly absorbent, friable and chalking substrates and cut edges of gypsum plasterboard with *decotric Deeply-Penetrating Primer LF* or *Primer PP*. Also pretreat sanded surfaces with *decotric Deeply-Penetrating Primer LF* or *decotric Gel Primer*. Pretreat non-absorbent, smooth or impervious substrates with a quartz-bearing primer.

Application:

Add 10 kg powder into a bucket with 6 l cool clean water and mix it. Stir compound again after 3 minutes. The filler remains processable for approx. 60 minutes. The application of a thick layer in one single workstep is possible. It will not shrink or crack when it dries. The filler is easy to smooth and after drying easy to sand. To avoid irregular drying of subsequent coatings on partial filled areas the filled spots or even the entire wall should be primed again with *decotric Primer – solvent-free* or *Power Primer PP*.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use at building fabric and room temperatures below + 5 °C

Clean tools with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in cool, dry place, out of reach of children.

Keep opened containers tightly closed.

Available sizes:

10 kg	4007955266051	026605001
20 kg	4007955266068	026606001

