

decomur Light Repair Filler

Use:

Ultra-light, white filling compound for patching cracks, holes and similar damaged areas indoors. For mineral substrates (e.g. plaster, render and concrete), glass fabrics, rigid foam, polystyrene and similar surfaces. Ideal for filling internal insulation board, stucco mouldings and decorative features.

Properties:

- easy workability
- sandable and overcoatable
- for indoor use

Technical data:

Raw material base: Polymer dispersion, water, inorganic lightweight fillers and additives
Density: Approx. 0.53 g/cm³
pH value: 7 – 9

Substrate preparation:

Substrate shall be dry, strong and free from dust and grease.

Application:

Knead tube well prior to use. Apply decomur Light Repair Filler up to max. coat thickness of 15 mm and smooth down. After full drying (up to 8 hours at +20 °C, depending on coat thickness), material is very easy to sand. decomur Light Repair Filler may serve as base for bonded, emulsion paint or lacquer finish.

Note:

Do not use at substrate and room temperatures below +10 °C. Wash tools with water immediately after use.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.decotric.de or from sds@decotric.de.

Storage:

Store in cool, though frost-free environment, in properly sealed containers, out of reach of children.

Disposal:

Hand over only fully emptied containers for recycling. Dried material residue may be disposed of as domestic or construction site waste. Dispose of uncured waste under EWC waste code: 08 04 10.

Item No.

108701001

EAN

4007955087014

Container size

225 ml



Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.