

Power Easy-Fill

- for indoors and outdoors
- fibre-reinforced for high stability
- weatherproof and moisture-resistant
- hardens crack-free
- can be sanded
- versatile

Instructions for use:

Power Easy-Fill is ideally suited for improving, smoothing and coating uneven, rough ceilings, walls and facades as well as for reliable, widespread filling and smoothing of pre-fabricated concrete elements, lime, cement and gypsum based plasters. Can also be used on all mineral surfaces (concrete, air-entrained concrete, clay tiles, etc.) as well as emulsion paints and gypsum boards. Not suitable for filling works on wood, metal, glass and plastic.

Technical specifications:

Components: Styrene-acrylate emulsion, fillers and additives
pH value: 8 -9
Density: 1,7 g/cm³
Usage: approx. 1.7 kg/m² for a 1 mm coat thickness

Substrate preparation:

Prime highly absorbent, sanding and chalking surfaces with *decotric Deeply Penetrating Primer – Solvent Free* or *Power Primer PP*.

The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *decotric Wallpaper Remover*. Make good cracks and holes using *Power MT 75*.

Application:

Apply *Power Easy-Fill* onto the surface up to a thickness of max. 5 mm using a smoothing trowel. Unevenness can be smoothed or felted over when moist. Do not apply subsequent coats of paint or adhesive until the filled area has completely dried. It is not necessary to prime the surface for subsequent wallpapering and painting works.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use if the surface and/or room temperature is less than +5° Celsius.

Clean tools in water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool but frost-free place! Keep the containers tightly sealed

Available sizes:

400g 033306173 4007955333760

