

Power Wood-Fill

- high filling capacity
- hardens evenly and crack-free
- remains slightly elastic after hardening
- can be sandpapered and overpainted
- for indoors and – with a weatherproof additional paint – also for outdoors

Instructions for use:

Power Wood-Fill is suited for filling and smoothing cracks and holes as well as cracked edges on wooden surfaces. Usable for indoors and - with a weatherproof additional paint - also for outdoors.

Technical specifications:

Components: Styrene acrylate emulsion, fillers, additives
 pH value: 9 – 10
 Density: 1.8 g/cm³
 Drying time: 6-12 hours, depending on the thickness of the layer, absorbency of the surface and ambient temperature
 Usage: approx. 1.8 kg/m² for 1 mm thick filler layer

Substrate preparation:

The surface must be dry, firm and free of release agents. Remove weathered wood up to the healthy layer.

Application:

Knead the tube well before use. Use a smoothing trowel to apply *Power Wood-Fill* with a layer up to max. 5 mm thick. Unevenness can be smoothed or felted over when moist. After the filled area has completely dried, *Power Wood-Fill* can be coated over with all water-based colours and lacquers.

When using *Power Wood-Fill* outdoors, apply a weather-proof additional paint after moist.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Do not use on surfaces or in rooms below + 5° Celsius!

Clean tools with water immediately after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Store in a cool, but frost-free place. Keep the containers tightly sealed!

Available sizes:

400 g 4007955082729 008202173

