POWER Wallcovering Adhesive GF

Technical Data Sheet

- EAN 4007955017738 / 5 kg
- EAN 4007955017752 / 18 kg

Ready-to-use emulsion adhesive for heavy wallpapers: suitable for textile wallpapers, vinyl wallpapers, non-woven wallpapers, and fiberglass wallpapers, as well as renovation and smooth non-woven wallpapers. The wallpaper adhesive can be used directly without mixing and is the ideal choice for wallpapering during renovations and wall design projects.

Features

- For heavy wall coverings, non-woven wallpaper, renovation non-woven, and smooth non-woven
- High moisture resistance
- Can be applied with a brush, roller, or airless sprayer
- Solvent-free

Applications

Ready-to-use emulsion adhesive for all heavy textile and vinyl wallpapers, as well as non-woven and fiberglass wallpapers, renovation non-woven, and smooth non-woven.

Preparation

The substrate must be sound, dry, level, uniformly absorbent, and free of dust and grease. Remove old wallpaper and poorly adhering paint. Fill cracks, holes, and uneven areas with spackle. Prime highly absorbent, sandy, and chalky substrates, as well as sanded surfaces, with decotric Deep Primer LF.

Application

Stir the adhesive thoroughly before use and apply it evenly to the substrate in strips the width of the wallpaper using a paste roller or brush. Place the cut strip into the fresh adhesive bed and press it down evenly and without air bubbles. Join the strips edge-to-edge. It is essential to follow the wall covering manufacturer's installation instructions. If specified by the manufacturer, apply the adhesive directly to the wall covering and install it after the prescribed open time. Do not paint the wall coverings with emulsion paint until the adhesive has dried completely. Working time: approx. 15 minutes, depending on the substrate and temperature.

Coverage

approx. 250 g/m² – depending on the substrate.

Storage

Store in a tightly sealed container, out of reach of children, in a cool but frost-free place.
Minimum shelf life: 48 months from the date of manufacture.

Notes

Do not apply at object or room temperatures below +5 °C. Remove adhesive residue immediately with water. Clean tools with water immediately after use.
Refer to the technical data sheet. For safety-related information, please consult the safety data sheet. Current safety data sheets are available on our website at www.decotric.de or at info@decotric.de.

decotric GmbH ■ Im Schedetal 1 ■ 34346 Hann. Münden ■ Website www.decotric.com

Note:

All information and data listed in this data sheet are based on our practical experience and laboratory tests and reflect the current state of the art. However, they are provided solely as general guidelines and do not constitute a guarantee of specific properties or performance characteristics. Since the conditions for storage, transport, and use of the products are beyond our control, no legal liability can be derived from the information presented here. It is the user's responsibility to verify the product's suitability for the intended purpose under the specific site or project conditions.